



Applications						
Frontlit	Banner	Billboard	Blockout	Awnings	Displays	Year-Round Canopies
●	●			●	●	●

Ink Compatibility <i>(all inks must be tested for compatibility)</i>					
Solvent	Eco Solvent	UV	Screen Printing	Eradicable	Latex
●	●	●	●		●

Not eradicable. **Decorative Methods:** P.S. Vinyl, Silk Screen, Spray Paint, and Digitally Printable.

.....

Coolley/Commercial Graphics
WHERE SUSTAINABLE CHEMISTRY MAKES THE DIFFERENCE

cooleygroup.com
info@cooleygroup.com


Global Headquarters and Manufacturing
50 Esten Avenue
Pawtucket, RI 02860, USA
+1 401.724.9000
Email: cginfo@cooleygroup.com

R&D Innovation Center and Manufacturing
5 Slater Road
Cranston, RI 02920, USA
+1 401.724.9000

Manufacturing
861 Quality Drive
Lancaster, SC 29720, USA
+1 803.289.1846

European Headquarters
In der Steinwiese 5
57074 Siegen
Germany
+49 (0) 271.770.1777






Burgundy **




Red *



Terracotta *




Sunflower Yellow *



Green *




Forest Green **



Blue **



Navy Blue *



Chocolate Brown *



Charcoal *



Linen **



White **



Dark Red **

Shown Above: Weathertyte® PLUS



Black **

Shown Above: Weathertyte® PLUS Lite

* Available in Weathertyte® PLUS

** Available in Weathertyte® PLUS and Weathertyte® PLUS Lite

Acrylic Topcoat

Weathertyte® PLUS 8-year Warranty

Weathertyte® PLUS Lite 5-year Warranty



WEATHERTYTE® PLUS

AWNING

Added Benefits:

- Embossed for high-quality, textured fabric look/feel
- Lightweight; improved flexibility
- Weather- and stain-resistant
- Watertight
- FR Certified

Weathertyte® PLUS is a premium textured vinyl substrate designed for use in banner, awning, marine, and other specialty applications. It is optimized for use with Solvent, UV, and Latex printers. This revolutionary material offers the look, feel, and texture of fabric and offers superior printability, weatherability, and strength.

Basic Fabric	Standard	Metric
Base Fabric Weight	2.7 oz/yd²	91 g/m²
Fiber / Style	Polyester Low Wick Scrim	

Coated Fabric	Standard	Metric
Total Weight (Weathertyte® PLUS)	16 oz/yd²	542 g/m²
Total Weight (Weathertyte® PLUS Lite)	11 oz/yd²	373 g/m²
Coating Type	PVC	
Sealing Properties	Dielectric	Thermal

Material Properties	ASTM Test Methods	Weathertyte® PLUS Standard Metric	Weathertyte® PLUS Lite Standard Metric
Tensile Strength, Grab (Warp)	D751-A	230 lbs 1,023 N	230 lbs 1,023 N
Tensile Strength, Grab (Fill)	D751-A	150 lbs 667 N	150 lbs 667 N
Tear Strength, Tongue (Warp)	D751-B (mod)	50 lbs 222 N	50 lbs 222 N
Tear Strength, Tongue (Fill)	D751-B (mod)	30 lbs 133 N	30 lbs 133 N
Screwdriver Puncture	D751	50 lbs 222 N	40 lbs 178 N
Ball Puncture	D751	250 lbs 1,112 N	240 lbs 1,068 N
Hydrostatic Resistance	D751-A	300 psi 2.1 MPa	250 psi 1.7 MPa
Abrasion Resistance	D3389	900 cycles	200 cycles
Low Temp Bend	D2136	0°F -18°C	-10°F -23°C
High Temp, Cont/Interm.	D1204	180 / 200°F 82 / 93°C	180 / 200°F 82 / 93°C
Mildew/Fungus Resistance	G21	No Growth	
Fire Resistance	E84 NFPA 701 (small scale) NFPA 701 (large scale)	Class A Pass Pass CA State Fire Marshall	

The information contained herein or that is supplied by us, or on our behalf, is based upon data obtained through our own research and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data, the results obtained from the use thereof, or that any such use will not infringe upon any patent. This information is furnished upon the condition that the person receiving it shall evaluate its suitability for the specific application.